

# FML250 Liquid Flow Monitor

**HIGHLY ACCURATE AND RELIABLE  
LIQUID MEASUREMENT DISPLAY**



**Turbines, Inc.** is the leader in the design and manufacture of reliable and accurate turbine flow metering equipment, electronic monitors, and accessories. All products are engineered, manufactured, and calibrated using premium quality materials by skilled tradesman with state-of-the-art equipment.

Turbines, Inc. maintains a team of dedicated engineers, technicians, and application specialists, who are on-call to assist with product/application guidance, technical assistance, and special configurations or modifications.

The **FML250 Flow Monitor** is designed to accurately compute and display actual flow parameters, which operates seamlessly for various application requirements. The FML250 monitor is front keypad programmable, features an LCD display, and allows for 2-40 point linearization for enhanced metering accuracy.

This battery powered monitor features a comprehensive test suite, featuring auto K-factor correction, 4-20mA and pulse output simulation, battery voltage, and raw meter input frequency.

## FML250 Features

<b>Factored pulse output</b>	(150mA, 30VDC max) Opto-isolated open collector output
Frequency or fixed pulse width	2, 5, 10, 50, 100, 250, 500, & custom mS
Pulse output divider	1, 10, 100, 1000, & custom
Pulse output multiplier	x100(0.01), x10(0.1)
<b>Factored rate output</b>	(4-20mA) Scalable low and high programmable Loop powered operation
<b>Display</b>	+/- 0.01% reading (rate) or +/- 1 count (total) Two independent lines for maximum display
<b>Rate display</b>	auto-ranging
<b>Power modes</b>	Selectable for custom battery life External loop powered and reverse polarity protected
<b>Temperature</b>	-22° F to +150° F
<b>Signal Input</b>	0-6000Hz, 50mV-36V (field adjustable)
<b>Input Impedance</b>	10k ohms
<b>Features</b>	Field-programmable
<b>Temp Compensation</b>	Optional PT100 - 2 Wire RTD Sensor

## Specifications

Performance Data	
Linearization	2-40 points
Refresh Rate	Continuous to 2 seconds
Pulse Input	Supports sine and square wave
Keypad	Front panel
Power	Battery powered operation and selectable power modes. Lithium primary D cell battery standard, alkaline 1.5 D clip available
Testing	Built-in test system for diagnostics, pulse output, and 4-20mA output testing
Display Rates	Per second, minute, hour, day, or custom
Maintenance	Automatic reminders and flow rate warnings
Materials	
Mounts	Direct turbine, wall, or pedestal
Weight	2 lbs
Storage	
	EEPROM parameter storage Secondary storage location for parameters and linearization table
Additional Information	
	Field-programmable
Engineering Units	GAL, CF, LIT, M3, LB, BBL, LBM KG, MCF

## FML250 Configurations

### FML250 - PXXX - X

#### Options

P = Scaleable Pulse Output (Standard)  
 4 = 4-20mA Loop Output  
 L = Linearization (2-40 points)  
 T = Temperature Compensation (includes 1000 ohm RTD & 36" temperature cable)

#### Mounting

Blank = Meter mount  
 SM = Swivel Mount  
 W = Wall Mount (Includes 30' Signal Cable)

**Example Part Number:** FML250 - PL - W = (FML250 with scaleable pulse output, linearization, wall mount).

## Service

Our dedicated staff offers complete support and recertification for flow meters — whether our own or a competitor's brand. Our calibration services are performed by our trained technicians using the latest testing equipment.

Turbines, Inc. maintains extensive inventories in multiple locations to facilitate rapid, industry leading deliveries.

## Worldwide Support

We serve customers globally with offices in Altus, OK; Seneca, SC; Odessa, TX; Cranston, RI; and Edmonton, Alberta, Canada.



All Turbines, Inc. products are proudly made in the U.S.A.



15935 Highway 283 N.  
 Altus, Oklahoma 73522, USA  
 Tel: +1-580-477-3067  
[www.turbinesincorporated.com](http://www.turbinesincorporated.com)



A wholly Owned Subsidiary of Turbines, Inc. Altus, OK, USA

112 Lumber Ln.  
 Seneca, SC 29672 USA  
 Tel: +1-864-882-4544  
[www.turbinesincorporated.com](http://www.turbinesincorporated.com)



960 South Meadow Ave.  
 Odessa, TX 79761 USA  
 Tel: +1-432-333-4800  
[www.turbinesodessa.com](http://www.turbinesodessa.com)



800 Wellington Avenue  
 Cranston, RI 02910, USA  
 Tel: +1-401-461-6366  
[www.primaryflowsignal.com](http://www.primaryflowsignal.com)



2236 80th Avenue NW,  
 Edmonton, AB T6P 1N2  
 Tel: 877-661-3569  
[www.pfscanada.com](http://www.pfscanada.com)